



RENEW

PRODUCT TYPE	Carpet Tile
CONSTRUCTION	Structured Loop
PILE FIBER COMPOSITION	bioloop™ SDN
TUFTING GAUGE	1/10"
PRIMARY BACKING	Non-Woven
SECONDARY BACKING	StableShield-100% Vinyl
TILE SIZE	19.6" x 19.6"
PILE HEIGHT	0.11in
TOTAL TILE HEIGHT	0.23in
PILE TREATMENT	Walk of Fame
SQUARE YARDS PER CARTON	6.0/yd ²
INSTALLATION METHODS	Carpet Tile

PERFORMANCE SPECIFICATIONS

WEAR SPECIFICATIONS	Heavy Contrast	
VOC (Green Label Plus)	ASTM D06-5116	<0.5 mg/m ² /hour
FLAMMABILITY (Pill Test)	ASTM D-2859-96	Pass 8/8
RADIANT PANEL	ASTM E-648	Class I
SMOKE DENSITY	ASTM E-662	<450
COLOR FASTNESS	AATCC/16	5/5 on Grey Scale
SOUND ABSORPTION VALUE	EN ISO 11654	α_w : 0.15 (H)
SOILING PROPENSITY	ASTM D 6540-00	4
DIMENSIONAL STABILITY	EN 986	<0.20%
CASTOR CHAIR TEST	DIN 54324	R $\geq$ 2.4



WWW.SPECTRUMCOLLECTIONFLOORING.COM

