

DURAMAX45

LUXURY VINYL PLANK



CLASSIFICATION	Vinyl Plank	Tile
SIZE	7.5" x 60"	18" x 36"
OVERALL THICKNESS	4.5 mm	
WEAR LAYER	22mil - PU with Ultimate Ceramic Beads	
EDGE	Micro Beveled	
INSTALLATION METHOD	Glue Down	
INSTALLATION GRADE	On Grade - Below Grade - Above Grade	
WARRANTIES (Limited)	Lifetime Waterproof / Lifetime Residential / 30 Year Commercial	
RECYCLED CONTENT	100% Recyclable Post	
RECOMMENDED ADHESIVE	Proma 8010 PSA / Bostik 449 PSA / Taylor Dynamic	
PACKAGING	PLANKS: 21.88 sqft per carton 55 Cartons per Pallet	TILE: 27.02 sqft per carton 46 Cartons per Pallet
WEIGHT PER CARTON	39 lbs	

PERFORMANCE SPECIFICATIONS

CRITICAL RADIANT FLUX	ASTM E648	Class 1
DENSITY OF SMOKE	ASTM E662	
FLAMING CONDITION	Corrected Max. Ds:	AVERAGE 425
NON-FLAMING CONDITION	Corrected Max. Ds:	AVERAGE 364
DIMENSIONAL STABILITY	ASTM F 2199-18	PASSED
FLEXIBILITY	ASTM 137	PASSED
RESISTANCE TO CHEMICALS	ASTM F925	SUPERIOR
RESISTANCE TO HEAT	ASTM F1514	PASSED
RESISTANCE TO LIGHT	ASTM F1515	PASSED
SOUND TESTING	ASTM E90 / E492	STC63/IIC52
STATIC LOAD RESISTANCE	ASTM F970	PASSED
TABOR ABRASION RESISTANCE	EN 13329	18000R
THICKNESS	ASTM F386	PASSED
SLIP RESISTANCE	Complies with ADA Guidelines	PASSED



WWW.SPECTRUMCOLLECTIONFLOORING.COM

