

RIGID CORE PLUS

LUXURY VINYL PLANK



CLASSIFICATION	Vinyl Plank	Vinyl Tile
SIZE	7" x 48"	12" x 24"
OVERALL THICKNESS	6 mm (4.5mm SPC + 1.5mm IXPE Pad)	
WEAR LAYER	22mil with Ultimate Ceramic Bead UV Coating	
EMBOSSING	Semi-EIR Registered Embossed	
INSTALLATION METHOD	Click	
SQAURE FEET PER CARTON	18.75 sqft per carton	20.75 sqft per carton
CARTONS PER PALLET	60 cartons per pallet	36 cartons per pallet
WEIGHT PER CARTON	43.15 lbs per carton	38.2 lbs per carton

PERFORMANCE SPECIFICATIONS

CHEMICAL RESISTANCE	ASTM F925 Superior	No Change
RESISTANCE TO HEAT	ASTM F1514 Meets	Meets < Delta E
CRITICAL RADIANT FLUX	ASTM E648	Class 1
SURFACE FLAMMABILITY	DOC FF - 1 - 70	Passes
FLEXIBILITY	ASTM 137	Passes
STATIC LOAD LIMIT	ASTM F970 .002 inch - Passed	250 PSI
STATIC COEFFICIENT OF FRICTION	ASTM2047	Passes
EMISSIONS TESTING	CAL 1350	Passes
SOUND RATING		64
TABOR ABRASION	ASTM D4060	18,000 Cycles

WARRANTY

LIMITED LIFETIME RESIDENTIAL

LIMITED 30-YEAR COMMERCIAL



WWW.SPECTRUMCOLLECTIONFLOORING.COM

