

CORPORATE II 36

COMMERCIAL BRADLOOM



PRODUCT TYPE	Broadloom
CONSTRUCTION	Tufted Broadloom
PRODUCT SIZE	12' Width (3.66 m)
SURFACE APPEARANCE	Cut Pile
TUFTED WEIGHT	36 oz/yd ² (1,221 g/m ²)
PRIMARY BACKING	Woven Primary
SECONDARY BACKING	Weldlok®
DENSITY	6,697
DYE METHOD	Piece Dyed
FIBER TYPE	Colorstrand® Nylon
GAUGE	1/10" (39.37 rows per 10 cm)
PATTERN REPEAT	N/A
STAIN RELEASE TECHNOLOGY	Protection Plus Stain
SOIL RELEASE TECHNOLOGY	Protection Plus Soil

PERFORMANCE SPECIFICATIONS

FLAMMABILITY	ASTM E 648 Class 1 (Glue Down)
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
INDOOR AIR QUALITY	Green Label Plus Certified #6678
NSF 140	Gold

WARRANTIES

LIFETIME LIMITED WEAR WARRANTY

LIFETIME LIMITED STATIC PROTECTION WARRANTY



WWW.SPECTRUMCOLLECTIONFLOORING.COM

