

RIGID CORE GENESIS

SPC FLOATING CLIC PLANK



CLASSIFICATION	SPC Vinyl Plank
SIZE	7" x 48"
OVERALL THICKNESS	5 mm (4.0mm SPC + 1.0mm IXPE Pad)
WEAR LAYER	22mil with Ultimate Ceramic Bead UV Coating
EMBOSSING	Semi-EIR Registered Embossed
INSTALLATION METHOD	Floating Clic (On, Above or Below Grade)
SQAURE FEET PER CARTON	23.64 sqft per carton
CARTONS PER PALLET	55 cartons per pallet
WEIGHT PER CARTON	39 lbs per carton

PERFORMANCE SPECIFICATIONS

CHEMICAL RESISTANCE	ASTM F925 Superior	No Change
RESISTANCE TO HEAT	ASTM F1514 Meets	Meets < Delta E
CRITICAL RADIANT FLUX	ASTM E648	Class 1
SURFACE FLAMMABILITY	DOC FF - 1 - 70	Passes
FLEXIBILITY	ASTM 137	Passes
STATIC LOAD LIMIT	ASTM F970 .002 inch - Passed	250 PSI
STATIC COEFFICIENT OF FRICTION	ASTM2047	Passes
EMISSIONS TESTING	CAL 1350	Passes
SOUND RATING		64
TABOR ABRASION	ASTM D4060	18,000 Cycles

WARRANTY

LIMITED 30-YEAR RESIDENTIAL

LIMITED 10-YEAR COMMERCIAL



RC Genesis
Installation
Guide



Spectrum
Flooring
Website

WWW.SPECTRUMCOLLECTIONFLOORING.COM

