

CLASSIFICATION	Vinyl Plank
SIZE	7" x 48"
OVERALL THICKNESS	6.0 mm
WEAR LAYER	20mil with Ultimate Ceramic Bead UV Coating
EDGE	Micro Beveled
INSTALLATION METHOD	SPC Floating Clic Flooring
INSTALLATION GRADE	On Grade - Below Grade - Above Grade
WARRANTIES (Limited)	Limited 10 Year Residential / Limited 30 Year Commercial
RECYCLED CONTENT	100% Recyclable Post
LOCKING SYSTEM	UNILIN Locking System
PACKAGING	PLANKS: 19.23 sqft per carton 8 Pieces Per Carton
WEIGHT PER CARTON	37.48 lbs

PERFORMANCE SPECIFICATIONS

CLASSIFICATION OF SMOKE	ASTM E648-10	Class 1
WEAR RESISTANCE	ASTM D4060	PASSED
CASTOR CHAIR TEST	NALFA LF 01-2011	PASSED
VERTICAL BURNING	UL 94 (2013)	PASSED
DIMENSIONAL STABILITY	ASTM F 2199-09	PASSED
FLEXIBILITY	ASTM 137	PASSED
RESISTANCE TO CHEMICALS	ASTM F925-13	PASSED
RESISTANCE TO HEAT	ASTM F1514	PASSED
RESISTANCE TO LIGHT	ASTM F1515	PASSED
STC RATING & SOUND TESTING	ASTM E90-09 / E492-09	STC70 / IIC73
STATIC LOAD RESISTANCE	ASTM F970-17	PASSED
PEEL RESISTANCE	ISO 24345-2006	PASSED
WEARLAYER THICKNESS	ASTM F410	PASSED
SLIP RESISTANCE	ASTM C1028-07	PASSED

